

# MAXFORCE e-Agitator™

*Built for the Way You Work*



## Ideal for Mobile Spray Applications

The MaxForce e-Agitator provides the same performance as pneumatic agitators but with the efficiency of an electric motor, making it the ideal choice for spray foam and polyurea contractors. The e-Agitator requires 110/120V, 4A, weighs only 16.5 lbs and plugs directly into your extension cord.

Ordering information:  
Standard S10442-15  
Elite S10442-20

**Power Requirements:**  
120VAC, 4A  
Speed Range: 0-500 RPM  
Mounting: 2" NPT Bung  
Weight: 16.5 lbs  
Wetted Materials: SST  
Not for use with solvents or materials with combustible vapors.  
Not rated for explosive atmospheres.



## Agitator Comparison Chart

	MaxForce e-Agitator	Pneumatic High Visc	Pneumatic Low Visc
Max Torque	56 in - lbs	55 in - lbs	20 in - lbs
Max RPM	500	500	500
CFM Requirement	0	22	12
Electrical Requirement	0.46 kW	N/A	N/A
Electrical Power Equivalent	0.46 kW	6.9 kW*	3.8 kW*
Weight	16.5	13.3	9.8
Fits in 2" NPT Bung	✓	✓	✓

\*Based on 3.2 cfm/kW reciprocating compressor

## Choose between Standard or Elite model

Additional features of Elite model:

- Maintains Agitator RPM as amount of material in drum changes
- Digital controller allows you to set the precise RPM you want



Distributed by:

CJ Spray, Inc  
651-455-0880  
2845 W Service Road  
Eagan, MN 55121

www.cjspray.com  
info@cjspray.com

www.maxforce.com  
info@maxforce.com  
1-888-4MaxForce  
(1-888-462-9367)  
Local: 651-789-8715

