MAXFORCE

RAS

Respiratory Alarm Shutoff

Built for the Way You Work

The Best and Fastest Way to Alert Spray Foam Applicators When Breathing Air Supply is Containated

The RAS connects to a high pressure breathing system such as a Bullard CAB panel or a Martech filtration panel, and is activated by the panels' audible CO alarm. When activated the RAS produces an error code on a Graco Reactor, which temporarily disables the machine. The applicator then vacates the spray area and removes the supplied air respirator.

The RAS solution prevents the need for costly remote audible alarms and provides a fail safe in the event that the audible alarm cannot be heard.

#515RAS-R1: for Graco E/H Reactors
#515RAS-R2: for Graco R2 E Reactors

RAS Features

- Works with all Graco Reactors
- Easy to install
- Works with all PPE CO monitor systems
- Works with dual proportioner rigs
- Eliminates the need for remote respiratory alarm
- Powered by CO monitor
- LED indicator (In event of audible alarm failure)

Works With: Bullard · ALLEGRO INDUSTRIES · MARTECH SERVICES COMPANY · AIR SYSTEMS INTERNATIONAL

Distributed by:

www.maxforce.com
info@maxforce.com
1-888-4MaxForce
(1-888-462-9367)
Local: 651-789-8715